

ZFA Quattro Power

Central filtration system with integrated limescale protection for single-family homes.

TWO FILTER STAGES · PFAS · ENK LIMESCALE PROTECTION

Three functions. One system.

1

FILTER 1

ITEM NO. 40.410

KDF and activated carbon: to reduce chlorine, selected heavy metals and organic trace substances.

2

FILTER 2

ITEM NO. 40.420

Anion exchanger and specialised activated carbon: to capture PFAS in drinking water.

E

ENK QUATTRO POWER

INTEGRATED

Limescale protection without regeneration salt. Calcium and magnesium remain in the water.

Activated carbon is also commonly used in water treatment to reduce pesticide residues. Its effectiveness depends on the substance, concentration and flow rate.



WATER FLOW

Main water connection → Filter 1 → Filter 2 → Home

CHOOSE YOUR MODEL

ZFA-01 Quattro Power

with ENK-01 · up to approx. 180 m²

Item no. 40.010

ZFA-02 Quattro Power

with ENK-02 · approx. 180–300 m²

Item no. 40.020

TECHNICAL DATA

Dimensions (H × W × D)	80 × 40 × 40 cm
Operating pressure	2–4 bar
Nominal flow rate	12.5 l/min
Water	Cold water, +2 to max. 23 °C
Weight	31.5 kg empty · approx. 50 kg in operation

Bypass connection	1½ in (union nut)
Installation site	Dry indoor space, 10–60 °C; load-bearing floor and floor drain.
Installation	Downstream of pressure-reducing valve, via bypass. Qualified plumber recommended.

FILTER REPLACEMENT

Replace both cartridges at least once a year. Depending on water consumption, an earlier replacement may be necessary. The display issues a reminder after no more than one year.